



**DS-2CC132P/132N Analog Camera
Special Mini Camera for ATM
Technical Manual**

Notices

The information in this documentation is subject to change without notice and does not represent any commitment on behalf of HIKVISION. HIKVISION disclaims any liability whatsoever for incorrect data that may appear in this documentation. The product(s) described in this documentation are furnished subject to a license and may only be used in accordance with the terms and conditions of such license.

Copyright © 2006-2010 by HIKVISION. All rights reserved.

This documentation is issued in strict confidence and is to be used only for the purposes for which it is supplied. It may not be reproduced in whole or in part, in any form, or by any means or be used for any other purpose without prior written consent of HIKVISION and then only on the condition that this notice is included in any such reproduction. No information as to the contents or subject matter of this documentation, or any part thereof, or arising directly or indirectly therefrom, shall be given orally or in writing or shall be communicated in any manner whatsoever to any third party being an individual, firm, or company or any employee thereof without the prior written consent of HIKVISION. Use of this product is subject to acceptance of the HIKVISION agreement required to use this product. HIKVISION reserves the right to make changes to its products as circumstances may warrant, without notice.

This documentation is provided "as-is," without warranty of any kind.

Please send any comments regarding the documentation to:
overseabusiness@hikvision.com

Find out more about HIKVISION at www.hikvision.com

Contents

1. Key Features
2. Specifications
3. Dimension

1. Key Features

- Compact Structure Design
- 1/4 inch CMOS
- Day / Night with Auto Switch
- Digital Signal Processing
- Auto White Balance, Auto Gain Control, Electronic Shutter Control, and Backlight Compensation
- Flickerless Mode
- CS Mount Lens (Provide Optional Adapter for C Mount Lens)
- Internal Synchronization
- Advanced Engineering Design, High Reliability

2. Specifications

Parameter	Model	DS-2CC132P/132N
Image Sensor		1/4 inch CMOS
Signal System		PAL/NTSC
Effective Pixels		640 (H) × 480 (V)
Min. Illumination		0.1Lux @ F1.2
Electronic Shutter Speed		1/25 s to 1/15,000 s
Lens Mount		C / CS mount
Auto Iris Lens		----
Day & Night		Electronic
Horizontal Resolution (TVL)		480 TVL
Synchronization		Internal synchronization
Video Output		1Vp-p Composite Output (75Ω/BNC)
S/N Ratio		More than 48dB
BLC		ON/OFF
Power Supply		12VDC, ±10%
Working Temperature		-10°C ~ 60°C (14°F ~ 140°F)
Power Consumption		2W MAX
Dimension (mm)		48 × 52 × 70
Weight		550g

3. Dimension

