



**DS-2CC192P(N) (-A) Analog Camera
Technical Manual**

Notices

The information in this documentation is subject to change without notice and does not represent any commitment on behalf of HIKVISION. HIKVISION disclaims any liability whatsoever for incorrect data that may appear in this documentation. The product(s) described in this documentation are furnished subject to a license and may only be used in accordance with the terms and conditions of such license.

Copyright © 2006-2010 by HIKVISION. All rights reserved.

This documentation is issued in strict confidence and is to be used only for the purposes for which it is supplied. It may not be reproduced in whole or in part, in any form, or by any means or be used for any other purpose without prior written consent of HIKVISION and then only on the condition that this notice is included in any such reproduction. No information as to the contents or subject matter of this documentation, or any part thereof, or arising directly or indirectly therefrom, shall be given orally or in writing or shall be communicated in any manner whatsoever to any third party being an individual, firm, or company or any employee thereof without the prior written consent of HIKVISION. Use of this product is subject to acceptance of the HIKVISION agreement required to use this product. HIKVISION reserves the right to make changes to its products as circumstances may warrant, without notice.

This documentation is provided "as-is," without warranty of any kind.

Please send any comments regarding the documentation to:
overseabusiness@hikvision.com

Find out more about HIKVISION at www.hikvision.com

Contents

1. Key Features
2. Specifications
3. Dimension




1. Key Features

- Compact Structure Design
- 1/3 Inch SONY CCD
- Day / Night with Auto Switch
- Auto White Balance, Auto Gain Control, Electronic Shutter Control, and Backlight Compensation
- Flickerless Mode
- Digital Signal Processing
- Auto Iris with DC / Video Driver
- CS Mount Lens (Provide Optional Adapter for C Mount Lens)
- Internal Synchronization
- Advanced Engineering Design, High Reliability

2. Specifications

Parameter	Model	DS-2CC192P(N)(-A)
Image Sensor		1/3 inch SONY Super HAD CCD
Signal System		PAL/NTSC
Effective Pixels		PAL: 752 (H) × 582 (V) NTSC: 768 (H) × 494 (V)
Min. Illumination		0.1Lux @ F1.2
Electronic Shutter Speed		1/50 (1/60) s to 1/100,000s
Lens Mount		C / CS mount
Auto Iris Lens		DC / Video
Day & Night		Electronic
Horizontal Resolution (TVL)		530 TVL
Synchronization		Internal synchronization
Video Output		1Vp-p Composite Output
S/N Ratio		More than 48dB
BLC		ON/OFF
Power Supply		12VDC, ±10%, "-A" series support 12VDC / 24V AC, ±10%.
Working Temperature		-10°C ~ 60°C (14°F ~ 140°F)
Power Consumption		2W MAX ("A" series 3.5MAX)
Dimension (mm)		63 × 59 × 114
Weight		550g

3. Dimension



Unit: (mm)