



**DS-2CD762MF-FB(H) IP Camera
Technical Manual**

Notices

The information in this documentation is subject to change without notice and does not represent any commitment on behalf of HIKVISION. HIKVISION disclaims any liability whatsoever for incorrect data that may appear in this documentation. The product(s) described in this documentation are furnished subject to a license and may only be used in accordance with the terms and conditions of such license.

Copyright © 2006-2010 by HIKVISION. All rights reserved.

This documentation is issued in strict confidence and is to be used only for the purposes for which it is supplied. It may not be reproduced in whole or in part, in any form, or by any means or be used for any other purpose without prior written consent of HIKVISION and then only on the condition that this notice is included in any such reproduction. No information as to the contents or subject matter of this documentation, or any part thereof, or arising directly or indirectly therefrom, shall be given orally or in writing or shall be communicated in any manner whatsoever to any third party being an individual, firm, or company or any employee thereof without the prior written consent of HIKVISION. Use of this product is subject to acceptance of the HIKVISION agreement required to use this product. HIKVISION reserves the right to make changes to its products as circumstances may warrant, without notice.

This documentation is provided "as-is," without warranty of any kind.

Please send any comments regarding the documentation to:
overseabusiness@hikvision.com

Find out more about HIKVISION at www.hikvision.com

Contents

1. Key Features
2. Specifications
3. Dimension

1. Key Features

- Linux OS Embedded
- TI DaVinci Hardware Compression
- H.264 / MPEG-4 Video Compression
- 1 Channel Audio Compression
- High Resolution Video Preview: 1600 × 1200 Pixels (752MF-FB), 1280 × 720 Pixels (762MF-FB)
- Support HD720 / 4CIF / DCIF / 2CIF / CIF / QCIF Real Time Compression
- Support SDHC Card for Local Recording
- Support Dual Compression Stream
- Support Motion Detection, and Notification on PC Client
- Support both Variable Bit Rate and Variable Frame Rate
- Support TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, PPPoE, etc.
- Support IE for Network Preview
- Support HIKVISION Watermark
- Support Sensor Alarm Input and Relay Output
- Support Network Intercom Function
- Support e-PTZ Function
- Compatible with Current SDK and Client Software
- Impact Protection: IEC60068-275 test, Eh, 50J; EN50102, exceeding IK10.

2. Specifications

Model	DS-2CD762MF-FB (H)	
Parameter		
Camera		
Image Sensor	1/3 inch SONY progressive scan CCD	
Effective Pixels	1280 (H) × 960 (V), 1.3M CCD	
Min. Illumination	0.1Lux @ F1.2	
Lens	3.3-12mm @ F1.4 /Auto Iris lens	
Day&Night	ICR	
Compression standard		
Video Compression	H.264 / MPEG-4	
Video Output	32 K ~ 2M, adjustable (8Mbps maximum)	
Audio Compression	OggVorbis	
Image		
Max. Image Resolution	1280 × 960	
Frame Rate	12.5fps (1280 × 960), 25fps (1280 × 720), 25fps (640 × 480)	
Function		
e-PTZ	---	
Motion Detect	Support	
Dual Stream	Support	
SD Card Local Recording	Support	
Heartbeat	Support	
Password Protect	Support	
Protocols	TCP / IP, HTTP, DHCP, DNS, RTP / RTCP, PPPoE (FTP, SMTP, NTP, SNMP addible)	
Interface		
Audio Input	1 channel(2.0 ~ 2.4Vp-p, 1kΩ)	
Audio Output	1channel (Line level, 600Ω)	
Communication	1 RJ45 10M / 100M self-adapted Ethernet port and, 1 RS-485 interface	
Alarm Input	1 channel signal input	
Alarm Output	1 channel signal Relay output	
Others		
Working Temperature	-10℃ ~ 60℃ ("H" series support-40℃ ~ 60℃)	
Power Supply	AC24V±10% / DC12V±10% , or PoE (Power over Ethernet)	
Power Consumption	5W (15W MAX heat)	
Heat / Scatter Heat	"H" series support	
Impact Protection	IEC60068-275Eh,50J;EN50102, exceeding IK10	

Water and Dust Resistance	IP66
Dimension(mm)	φ156 × 134.5
Weight	1400g

3. Dimension

